

View Online at <https://aerobasegroup.com/nsn/5930-01-123-1471>

**Thread Class:**

2a

**Hazardous Locations/environmental Protection:**

Watertight

**Bushing Length:**

0.562 inches

**Body Length:**

0.690 inches

**Body Width:**

0.850 inches

**Body Height:**

0.380 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.125 inches

**Actuator Height:**

0.320 inches

**Actuator Free Position Height:**

0.882 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

6625-01-034-0942

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.375 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

8.0 ounces

**Switch Actuating Force:**

40.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.187 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes motor dc

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 tab, solder lug

**Specification Data:**

81349-mil-s-8805/84 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0