NSN 5930-01-123-2912

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-123-2912

| Overall Length: |
|--|
| 0.308 inches |
| Overall Height: |
| 0.294 inches |
| Body Diameter: |
| 0.215 inches |
| Body Height: |
| 0.136 inches |
| End Application: |
| Radar |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Operating Tempurature Rating: |
| Between -30.0 degrees fahrenheit and 350.0 degrees fahrenheit |
| Mounting Method: |
| Clamp |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Increase |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Load Current Rating: |
| 500.0 milliamperes resistive load second voltage |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Stimulus Rating: |
| 225.00 actuation point degrees fahrenheit and 195.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level second voltage |
| Frequency In Hertz: |
| 60.0 first voltage |
| Media For Which Designed: |
| Gas or liquid |
| Style Designator: |
| Disc |
| Test Data Document: |
| 81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

81349-mil-s-24236/19 government specification

Specification Data:

NSN 5930-01-123-2912

Thermostatic Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0