

View Online at <https://aerobasegroup.com/nsn/5930-01-123-2914>

**Body Style:**

Bushing mount

**Overall Length:**

1.125 inches

**Overall Height:**

2.733 inches

**Overall Width:**

0.750 inches

**Bushing Length:**

0.468 inches

**Body Length:**

1.125 inches

**Body Width:**

0.750 inches

**Body Height:**

1.000 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.420 inches

**Actuator Height:**

1.140 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position no locking action and down position no locking action and center position locked in

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Generator

**Mounting Surface To Terminal End Distance:**

1.125 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

8 two circuit, double break/double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 1.000 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes motor dc

**Precious Material And Location:**

Contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

32 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0