

View Online at <https://aerobasegroup.com/nsn/5930-01-123-2915>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Body Diameter:**

1.000 inches

**Bushing Length:**

0.470 inches

**Body Length:**

2.560 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

1.160 inches

**Actuator Position-action Relationship:**

Center position maintained and left position maintained and right position maintained

**Actuator Color:**

Gray single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

Generator

**Mounting Surface To Terminal End Distance:**

2.350 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 2.000 amperes inductive dc

**Special Features:**

Holding coil

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0