

View Online at <https://aerobasegroup.com/nsn/5930-01-123-2915>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Body Diameter:

1.000 inches

Bushing Length:

0.470 inches

Body Length:

2.560 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

1.160 inches

Actuator Position-action Relationship:

Center position maintained and left position maintained and right position maintained

Actuator Color:

Gray single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Generator

Mounting Surface To Terminal End Distance:

2.350 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 2.000 amperes inductive dc

Special Features:

Holding coil

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0