NSN 5930-01-123-4183

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-123-4183

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
6.680 inches
Overall Height:
2.600 inches
Overall Width:
1.600 inches
Actuator Length:
2.750 inches
Actuator Style:
Roller arm
Actuator Height:
1.125 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.281 inches
Housing Height:
1.890 inches
Housing Length:
4.180 inches
Housing Width:
1.600 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
600.0 ac and 480.0 dc
End Application:
Hull obrp
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

NSN 5930-01-123-4183

Sensitive Switch - Page 2 of 2

A053a0



Switch Actuating Force:
24.0 inch-ounces
Actuator Movement:
12.0 pretravel degrees and 40.0 overtravel degrees and 5.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
100.000 milliamperes resistive dc and 1.200 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: