

View Online at <https://aerobasegroup.com/nsn/5930-01-123-5230>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.219 inches

Overall Height:

3.516 inches

Overall Width:

2.766 inches

Distance Between Mounting Facility Centers:

1.750 inches

Capillary Tube Length:

36.0 inches

Bulb Length:

11.625 inches

Bulb Diameter:

0.188 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Base and threaded hole

Features Provided:

Automatic reset

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

25.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+200.00/+550.00 actuation point degrees fahrenheit and +200.00/+550.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft with scale and external actuation point shaft with scale

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0