

View Online at <https://aerobasegroup.com/nsn/5930-01-123-5230>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.219 inches

**Overall Height:**

3.516 inches

**Overall Width:**

2.766 inches

**Distance Between Mounting Facility Centers:**

1.750 inches

**Capillary Tube Length:**

36.0 inches

**Bulb Length:**

11.625 inches

**Bulb Diameter:**

0.188 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Mounting Method:**

Base and threaded hole

**Features Provided:**

Automatic reset

**Thready Qty Per Inch (tpi):**

32 all threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.138 inches all threaded hole

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

25.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+200.00/+550.00 actuation point degrees fahrenheit and +200.00/+550.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point shaft with scale and external actuation point shaft with scale

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0