NSN 5930-01-123-5368

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-123-5368

Thread Class: 2b single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 4.031 inches **Overall Height:** 2.500 inches First Flat Length: 0.750 inches single actuator Flat Height: 0.219 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.000 inches single actuator **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Longest Horizontal Distance Between Mounting Centers:** 1.641 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 1.641 inches single mounting facility **End Application:** Hull obrp **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 1 each section rear **Mounting Method:** Threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 40 single mounting facility **Thread Size:**

0.112 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

NSN 5930-01-123-5368

Rotary Switch - Page 2 of 2



Mounting Facility Pattern: Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round, flatted, threaded hole single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 90.0 degrees single actuator **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 10.0 amperes resistive load ac at sea level **Style Designator:** Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A052b0