NSN 5930-01-123-6513

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-123-6513

| Body Style: |
|--|
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Bushing Length: |
| 0.469 inches |
| Body Length: |
| 0.562 inches |
| Body Width: |
| 0.354 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.240 inches |
| Actuator Height: |
| 0.687 inches |
| Actuator Position-action Relationship: |
| Left position maintained and right position maintained |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| End Application: |
| Control |
| Mounting Surface To Terminal End Distance: |
| 0.706 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 2.000 amperes resistive dc |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |

N/a

NSN 5930-01-123-6513 Toggle Switch - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

Demilitarization:

No

Fiig:

A053a0