NSN 5930-01-123-8283

Slide Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-123-8283

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.406 inches
Body Width:
0.531 inches
Body Height:
0.328 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Length:
0.281 inches
Actuator Height:
0.344 inches
Actuator Width:
0.219 inches
Actuator Position-action Relationship:
Center position maintained and left position maintained and right position maintained
Actuator Position-locking Relationship:
·
Center position locked in and left position locked in and right position locked in
Center position locked in and left position locked in and right position locked in
Center position locked in and left position locked in and right position locked in Actuator Color:
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts:
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage:
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location:
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location: Terminals and contacts silver
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location: Terminals and contacts silver Terminal Type And Quantity:
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location: Terminals and contacts silver Terminal Type And Quantity: 8 printed circuit
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location: Terminals and contacts silver Terminal Type And Quantity: 8 printed circuit Shelf Life:
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location: Terminals and contacts silver Terminal Type And Quantity: 8 printed circuit Shelf Life: N/a
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location: Terminals and contacts silver Terminal Type And Quantity: 8 printed circuit Shelf Life: N/a
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location: Terminals and contacts silver Terminal Type And Quantity: 8 printed circuit Shelf Life: N/a Unit Of Measure:
Center position locked in and left position locked in and right position locked in Actuator Color: Black single actuator Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Contact Load Current Rating At Maximum Rated Voltage: 5.000 amperes resistive dc and 3.000 amperes resistive ac Precious Material And Location: Terminals and contacts silver Terminal Type And Quantity: 8 printed circuit Shelf Life: N/a Unit Of Measure: Demilitarization: