

View Online at <https://aerobasegroup.com/nsn/5930-01-123-8575>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.187 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

1.499 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.094 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.399 inches single actuator

**Overall Diameter:**

0.920 inches

**Nonturn Device Radius:**

0.260 inches at 3: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 3: 00 o'clock

**End Application:**

Intg comm

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

22 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Pin

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

16.3 degrees single actuator

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0