

View Online at <https://aerobasegroup.com/nsn/5930-01-123-8575>

Thread Class:

2a single mounting facility

Thread Length:

0.187 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.499 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.094 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.399 inches single actuator

Overall Diameter:

0.920 inches

Nonturn Device Radius:

0.260 inches at 3: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3: 00 o'clock

End Application:

Intg comm

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

22 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Pin

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

16.3 degrees single actuator

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0