

View Online at <https://aerobasegroup.com/nsn/5930-01-123-9388>

Thread Class:

3a single pressure connection

Overall Length:

3.750 inches

Outside Diameter:

0.438 inches single connection

Body Diameter:

0.800 mils

Body Length:

2.440 inches

Overall Diameter:

0.880 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

7500.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

4.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage and 0.4 amperes inductive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

2400.00 actuation point pounds per square inch gage and 1950.00 deactuation point pounds per square inch gage and 2000.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Flareless, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unjf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0