NSN 5930-01-123-9530

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-123-9530

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.364 inches **Overall Height:** 1.843 inches **Overall Width:** 1.281 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.125 inches single actuator **Nonturn Device Radius:** 0.531 inches at 8: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Pin at 8: 00 o'clock **End Application:** Module ms anl **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Shaft Flat/slot Angular Location:** 75.0 degrees from nonturn device single actuator **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round, slotted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 30.0 degrees single actuator

NSN 5930-01-123-9530

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 1.0 amperes resistive load ac at sea level Precious Material And Location: Contact surfaces gold and contacts silver Precious Material: Gold and silver Style Designator: Circular wafer, bushing mount Thread Series Designator: Unef single mounting facility Shelf Life: N/a Unit Of Measure: --

Demilitarization:

No Fiig: A052b0