NSN 5930-01-123-9959

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-123-9959

External actuation point dial and external deactuation point dial

Overall Length:
4.218 inches
Overall Height:
2.031 inches
Overall Width:
2.562 inches
Mounting Slot Width:
0.115 inches
Body Length:
1.906 inches
Distance Between Mounting Facility Centers:
1.750 inches
End Application:
Hull obrp
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Bracket and slot
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
40.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.00/+20.00 actuation point pounds per square inch and +0.00/+20.00 deactuation point pounds per square inch
Contact Adjustment Type:

NSN 5930-01-123-9959

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0