## NSN 5930-01-123-9990

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-123-9990

#### Body Style:

Bushing mounted

#### **Body Diameter:**

1.500 inches

## Bushing Length:

1.000 inches

#### Body Length:

1.500 inches

#### Actuator Style:

Roller plunger

#### Actuator Free Position Height:

1.781 inches

#### Actuator Roller Diameter:

0.500 inches

#### Actuator Roller Width:

0.120 inches

## Maximum Voltage Rating In Volts:

28.0 dc

#### **End Application:**

Hull obrp

#### Inclosure Type:

Fully enclosed

#### Mounting Method:

Threaded bushing

#### Thread Size:

0.625 inches

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary, two positions maintained single switch unit

#### Switch Release Force:

60.0 ounces

#### Switch Actuating Force:

192.0 ounces

#### **Actuator Movement:**

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.030 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc

## **Thread Series Designator:**

Unef

## Terminal Type And Quantity:

6 wire lead

### Shelf Life:

N/a

# NSN 5930-01-123-9990

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

