

View Online at <https://aerobasegroup.com/nsn/5930-01-124-0561>

Thread Class:

3a single pressure connection

Overall Length:

3.528 inches

Outside Diameter:

0.438 inches single connection

Body Length:

2.250 inches

Overall Diameter:

1.120 inches

End Application:

Hull obrp

Pressure Switch Type:

Gage

Mounting Method:

Terminal, wire-lead

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

100.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

150.00 pounds per square inch gage

Terminal Type:

Wire hook

Contact Load Current Rating:

0.5 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

18.00 actuation point pounds per square inch gage and 15.00 deactuation point pounds per square inch gage and 3.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

50.0 dc at sea level second voltage

Pressure Connector Type:

Swivel nut, inverted flare, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0