NSN 5930-01-124-1393

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-124-1393

Overall Length:
Any acceptable
Ac Voltage Rating:
50.0 volts
Dc Voltage Rating:
50.0 volts
Frequency Rating:
60.0 hertz
Overall Diameter:
6.000 inches
Connector Manufacturer Code:
04034
Actuation Method:
Buoyancy
Electrical Connection Type:
Connector receptacle
Connector Identification:
38181
Current Rating At Maximum Rated Voltage:
0.06 amperes resistive load and 0.04 amperes resistive load
Voltage Rating At Maximum Rated Current:
50.0 volts
Float Quantity:
2
Operating Tempurature Rating:
Between 0.0 degrees fahrenheit and 180.0 degrees fahrenheit
Mounting Method:
Flange
Mounting Position:
Horizontal
Maximum Current Rating:
0.3 amperes resistive load
Contact Arrangement:
Spst, normally closed
Relay:
Not included
Liquid Type For Which Designed:
Hydraulic oil and lubricating oil and sea water and various fuels
Float Effective Travel:
Any acceptable
Mounting Dimensions:

Mtd by four 0.750 in. Diameter holes equally spaced on a 4.750 in. Diameter bolt circle

NSN 5930-01-124-1393

Liquid Level Switch - Page 2 of 2



Tank	Inserti	ion I d	anath:
ıanık	mserti	ION L	anatn.

22.270 inches

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T109-d