

View Online at <https://aerobasegroup.com/nsn/5930-01-124-1393>

Overall Length:

Any acceptable

Ac Voltage Rating:

50.0 volts

Dc Voltage Rating:

50.0 volts

Frequency Rating:

60.0 hertz

Overall Diameter:

6.000 inches

Connector Manufacturer Code:

04034

Actuation Method:

Buoyancy

Electrical Connection Type:

Connector receptacle

Connector Identification:

38181

Current Rating At Maximum Rated Voltage:

0.06 amperes resistive load and 0.04 amperes resistive load

Voltage Rating At Maximum Rated Current:

50.0 volts

Float Quantity:

2

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 180.0 degrees fahrenheit

Mounting Method:

Flange

Mounting Position:

Horizontal

Maximum Current Rating:

0.3 amperes resistive load

Contact Arrangement:

Spst, normally closed

Relay:

Not included

Liquid Type For Which Designed:

Hydraulic oil and lubricating oil and sea water and various fuels

Float Effective Travel:

Any acceptable

Mounting Dimensions:

Mtd by four 0.750 in. Diameter holes equally spaced on a 4.750 in. Diameter bolt circle

Tank Insertion Length:

22.270 inches

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T109-d