

View Online at <https://aerobasegroup.com/nsn/5930-01-124-1393>

**Overall Length:**

Any acceptable

**Ac Voltage Rating:**

50.0 volts

**Dc Voltage Rating:**

50.0 volts

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

6.000 inches

**Connector Manufacturer Code:**

04034

**Actuation Method:**

Buoyancy

**Electrical Connection Type:**

Connector receptacle

**Connector Identification:**

38181

**Current Rating At Maximum Rated Voltage:**

0.06 amperes resistive load and 0.04 amperes resistive load

**Voltage Rating At Maximum Rated Current:**

50.0 volts

**Float Quantity:**

2

**Operating Temperature Rating:**

Between 0.0 degrees fahrenheit and 180.0 degrees fahrenheit

**Mounting Method:**

Flange

**Mounting Position:**

Horizontal

**Maximum Current Rating:**

0.3 amperes resistive load

**Contact Arrangement:**

Spst, normally closed

**Relay:**

Not included

**Liquid Type For Which Designed:**

Hydraulic oil and lubricating oil and sea water and various fuels

**Float Effective Travel:**

Any acceptable

**Mounting Dimensions:**

Mtd by four 0.750 in. Diameter holes equally spaced on a 4.750 in. Diameter bolt circle

**Tank Insertion Length:**

22.270 inches

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T109-d