

<b>NSN 5930-01-124-1393</b> Liquid Level Switch - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5930-01-124	-139
Overall Length:	
Any acceptable	
Ac Voltage Rating:	
50.0 volts	
Dc Voltage Rating:	
50.0 volts	
Frequency Rating:	
60.0 hertz	
Overall Diameter:	
6.000 inches	
Connector Manufacturer Code:	
04034	
Actuation Method:	
Buoyancy	
Electrical Connection Type:	
Connector receptacle	
Connector Identification:	
38181	
Current Rating At Maximum Rated Voltage:	
0.06 amperes resistive load and 0.04 amperes resistive load	ł
Voltage Rating At Maximum Rated Current:	
50.0 volts	
Float Quantity:	
2	
Operating Tempurature Rating:	
Between 0.0 degrees fahrenheit and 180.0 degrees fahrenh	eit
Mounting Method:	
Flange	
Mounting Position:	
Horizontal	
Maximum Current Rating:	
0.3 amperes resistive load	
Contact Arrangement:	
Spst, normally closed	
Relay:	
Not included	
Liquid Type For Which Designed:	
Hydraulic oil and lubricating oil and sea water and various fu	رماد
Float Effective Travel:	1013
Any acceptable	

## **Mounting Dimensions:**

Mtd by four 0.750 in. Diameter holes equally spaced on a 4.750 in. Diameter bolt circle

## NSN 5930-01-124-1393

Liquid Level Switch - Page 2 of 2

Tank Insertion Length:

22.270 inches

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

T109-d

