

View Online at <https://aerobasegroup.com/nsn/5930-01-124-2479>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Body Length:

1.660 inches

Body Width:

0.520 inches

Body Height:

1.300 inches

Unthreaded Mounting Hole Diameter:

0.138 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

End Application:

Hull obrp

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

125.0 inch-ounces

Switch Actuating Force:

203.0 inch-ounces

Actuator Movement:

250.0 pretravel millimeters and 187.0 overtravel millimeters and 63.0 differential millimeters

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0