NSN 5930-01-124-2479

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-124-2479

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Body Length:
1.660 inches
Body Width:
0.520 inches
Body Height:
1.300 inches
Unthreaded Mounting Hole Diameter:
0.138 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.375 inches
Actuator Free Position Height:
0.375 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
End Application:
Hull obrp
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
125.0 inch-ounces
Switch Actuating Force:
203.0 inch-ounces
Actuator Movement:

250.0 pretravel millimeters and 187.0 overtravel millimeters and 63.0 differential millimeters

NSN 5930-01-124-2479

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0