# NSN 5930-01-124-7267

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-124-7267

#### **Thread Class:**

2a all threaded stud

## Thread Length:

0.187 inches all threaded stud

# **Overall Height:**

0.614 inches

#### **Body Height:**

0.216 inches

#### **Overall Diameter:**

0.215 inches

**End Application:** 

7021-01-107-2285

**Tempurature Sensing Element Type:** 

#### Internal sensor

**Mounting Method:** 

# Threaded stud

Thready Qty Per Inch (tpi):

40 all threaded stud

#### **Contact Action Stimulus:**

Increase

## Thread Size:

0.112 inches all threaded stud

## Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

#### **Terminal Type:**

Tab, solder lug

## **Contact Load Current Rating:**

1.0 amperes resistive load first voltage

## Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

#### **Contact Stimulus Rating:**

250.00 actuation point degrees fahrenheit and 220.00 deactuation point degrees fahrenheit

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

# Frequency In Hertz:

60.0 first voltage

# Media For Which Designed:

Gas or liquid

# Style Designator:

Disc

# **Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5930-01-124-7267

Thermostatic Switch - Page 2 of 2



**Thread Series Designator:** 

Unc all threaded stud

## **Specification Data:**

81349-mil-s-24236/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0