

View Online at <https://aerobasegroup.com/nsn/5930-01-124-9348>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.937 inches

Overall Height:

2.312 inches

Overall Width:

1.750 inches

First Flat Length:

0.125 inches 2nd actuator

Flat Height:

0.094 inches 2nd actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.500 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 9: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 9: 00 o'clock

End Application:

Ts3615/alq136

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

18 each section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 highest dc voltage rating at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

18 all actuators

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

20.0 degrees all actuators

Contact Load Current Rating:

750.0 milliamperes inductive load lowest dc voltage rating at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0