NSN 5930-01-125-0967



Rotary Switch - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5930-01-125-0967	
Thread Class:	
2b single mounting facility	
Overall Length:	
3.310 inches	
Overall Height:	
2.531 inches	
Overall Width:	
1.937 inches	
First Flat Length:	
0.250 inches single actuator	
Flat Height:	
0.218 inches single actuator	
Shaft Diameter:	
0.250 inches single actuator	
Shaft Length:	
0.500 inches single actuator	
Individual Section Quantity:	
2	
Longest Horizontal Distance Between Mounting Centers:	
2.219 inches single mounting facility	
End Application:	
Maint set	
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Pole Quantity:	
1 each section rear	
Throw Quantity:	
3 each section rear	
Mounting Method:	
Threaded hole single mounting facility	

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

NSN 5930-01-125-0967

Rotary Switch - Page 2 of 2



Shaft Type:		
Round, flatted single actuator		
Terminal Type:		
Tab, solder lug		
Contact Switching Action:		
Breaks before makes each section rear		
Switch Actuator Positioning Increment:		
30.0 degrees single actuator		
Switch Actuator Stop Device Type:		
Fixed stop single actuator		
Contact Load Current Rating:		
10.0 amperes resistive load ac at sea level		
Precious Material And Location:		
Current carrying members surfaces silver		
Precious Material:		
Silver		
Style Designator:		
Circular wafer, panel mount		
Thread Series Designator:		
Unc single mounting facility		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		
A052b0		