

View Online at <https://aerobasegroup.com/nsn/5930-01-125-5506>

Body Style:

Bushing/hole mounted

Overall Length:

0.781 inches

Overall Height:

1.187 inches

Overall Width:

0.375 inches

Bushing Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.375 inches

Actuator Style:

Round

Actuator Diameter:

0.125 inches

Actuator Height:

0.156 inches

Actuator Free Position Height:

0.531 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

0.375 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Off avionics/c

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

15.0 ounces

Switch Actuating Force:

18.0 ounces

Actuator Movement:

Between 0.062 pretravel inches and 0.109 overtravel inches and 0.031 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0