

View Online at <https://aerobasegroup.com/nsn/5930-01-125-5506>

**Body Style:**

Bushing/hole mounted

**Overall Length:**

0.781 inches

**Overall Height:**

1.187 inches

**Overall Width:**

0.375 inches

**Bushing Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.375 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.125 inches

**Actuator Height:**

0.156 inches

**Actuator Free Position Height:**

0.531 inches

**Actuator Adapter Style:**

Pushbutton

**Adapter Bushing Length:**

0.375 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

Off avionics/c

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing and unthreaded hole

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

15.0 ounces

**Switch Actuating Force:**

18.0 ounces

**Actuator Movement:**

Between 0.062 pretravel inches and 0.109 overtravel inches and 0.031 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0