## NSN 5930-01-125-5506

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-125-5506

Body Style:
Bushing/hole mounted
Overall Length:
0.781 inches
Overall Height:
1.187 inches
Overall Width:
0.375 inches
Bushing Length:
0.375 inches
Body Length:
0.781 inches
Body Width:
0.375 inches
Actuator Style:
Round
Actuator Diameter:
0.125 inches
Actuator Height:
0.156 inches
Actuator Free Position Height:
0.531 inches
Actuator Adapter Style:
Pushbutton
Adapter Bushing Length:
0.375 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
End Application:
Off avionics/c
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing and unthreaded hole
Thready Qty Per Inch (tpi):
40
Thread Size:
0.250 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit

15.0 ounces

**Switch Release Force:** 

## NSN 5930-01-125-5506

Sensitive Switch - Page 2 of 2

A053a0



Switch Actuating Force:
18.0 ounces
Actuator Movement:
Between 0.062 pretravel inches and 0.109 overtravel inches and 0.031 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: