

View Online at <https://aerobasegroup.com/nsn/5930-01-126-2877>

Body Style:

Hole mounted

Overall Length:

0.510 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.281 inches

Overall Height:

0.570 inches

Overall Width:

0.156 inches

Body Length:

0.510 inches

Body Width:

0.156 inches

Body Height:

0.350 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.093 inches

Actuator Height:

0.065 inches

Actuator Free Position Height:

0.355 inches

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Envir system

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

8.0 ounces

Actuator Movement:

Between 0.004 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc

Precious Material And Location:

Terminal surfaces gold and contacts silver

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 turret

Specification Data:

81349-mil-s-8805/101 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0