## NSN 5930-01-126-2880

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-126-2880

Body Style:
Hole mounted
Overall Length:
2.156 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.938 inches
Overall Height:
0.617 inches
Overall Width:
0.530 inches
Body Length:
1.750 inches
Body Width:
0.530 inches
Body Height:
0.307 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Switch Actuator Quantity:
2
Actuator Width:
0.234 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
End Application:
Comm central
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
500.000 milliamperes resistive dc and 3.000 amperes resistive ac
Precious Material And Location:
Terminal surfaces silver
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-01-126-2880

Slide Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0