## NSN 5930-01-126-3457

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-126-3457

Thread Class:
3a single pressure connection
Overall Length:
3.750 inches
Outside Diameter:
0.438 inches single connection
Body Diameter:
0.800 mils
Body Length:
2.370 inches
Overall Diameter:
0.880 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit
Mounting Method:
Inlet connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary
Sensing Element Burst Pressure:
7500.00 pounds per square inch gage
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
4.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage and 0.4 amperes lamp load second voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:

#### contact climates realing.

2400.00 actuation point pounds per square inch gage and 1950.00 deactuation point pounds per square inch gage and 2000.00 deactuation point pounds per square inch gage

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

#### **Pressure Connector Type:**

Flareless, threaded external single connection

#### Media For Which Designed:

Gas or liquid

# **NSN 5930-01-126-3457**Pressure Switch - Page 2 of 2



Style Designator:
Cylindrical
Thread Series Designator:
Unjf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0