

View Online at <https://aerobasegroup.com/nsn/5930-01-126-3459>

**Thread Class:**

3a single pressure connection

**Overall Length:**

3.750 inches

**Outside Diameter:**

0.438 inches single connection

**Body Diameter:**

0.800 mils

**Body Length:**

2.440 inches

**Overall Diameter:**

0.880 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Mounting Method:**

Inlet connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

7500.00 pounds per square inch gage

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

4.0 amperes resistive load second voltage and 3.0 amperes inductive load second voltage and 0.4 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

750.00 actuation point pounds per square inch gage and 580.00 deactuation point pounds per square inch gage and 620.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Pressure Connector Type:**

Flareless, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unjf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0