# NSN 5930-01-126-5324

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-126-5324

## **Thread Class:**

2a single mounting facility

### Thread Length:

0.312 inches single mounting facility

# **Overall Length:**

1.257 inches

#### Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

#### Shaft Length:

0.750 inches single actuator

#### **Overall Diameter:**

1.322 inches

#### **Nonturn Device Radius:**

0.531 inches at 3: 00 o'clock

#### Individual Section Quantity:

1

#### Nonturn Device Type:

Tab at 3: 00 o'clock

## **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

# End Application:

Comm central

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

300.0 ac at sea level

#### Switch Actuator Indexing Position Quantity:

5 single actuator

#### Shaft Type:

Round single actuator

# **Terminal Type:**

Printed circuit

#### **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

36.0 degrees single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-01-126-5324

Rotary Switch - Page 2 of 2



# **Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

### Style Designator:

Snap or line

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A052b0