NSN 5930-01-126-8879



| Pressure Switch - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5930-01-126-8879 |
| Thread Class: |
| 3b all pressure connection |
| Inside Diameter: |
| 0.750 inches all connections |
| Hazardous Locations/environmental Protection: |
| Moisture proof |
| Overall Length: |
| 3.250 inches |
| Overall Height: |
| 2.935 inches |
| Overall Width: |
| Between 0.970 inches and 1.280 inches |
| Body Height: |
| 1.875 inches |
| End Application: |
| Oe236delta81 |
| Pressure Switch Type: |
| Gage |
| Operating Tempurature Rating: |
| Between -40.0 degrees celsius and 100.0 degrees celsius |
| Mounting Method: |
| Inlet connection and outlet connection |
| Features Provided: |
| Electrical box connector |

Thready Qty Per Inch (tpi):

16 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.750 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

250.0 milliamperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

4.50 actuation point gallons per minute and 0.50 differential point gallons per minute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

NSN 5930-01-126-8879Pressure Switch - Page 2 of 2



| Pressure Connector Type: |
|--|
| Plain, threaded internal all connections |
| Media For Which Designed: |
| Liquid |
| Style Designator: |
| Rectangular |
| Thread Series Designator: |
| Unf all pressure connection |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A048b0