

View Online at <https://aerobasegroup.com/nsn/5930-01-126-8880>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Height:

9.906 inches

Overall Width:

3.813 inches

Body Height:

6.375 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

3.626 inches

Longest Vertical Distance Between Mounting Centers:

3.626 inches

End Application:

4935-01-098-3966

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 400.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port and tamper proof cap

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+100.00/+225.00 actuation point degrees fahrenheit and +99.00/+222.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0