

View Online at <https://aerobasegroup.com/nsn/5930-01-126-8880>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Height:**

9.906 inches

**Overall Width:**

3.813 inches

**Body Height:**

6.375 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.626 inches

**Longest Vertical Distance Between Mounting Centers:**

3.626 inches

**End Application:**

4935-01-098-3966

**Temperature Sensing Element Type:**

Bulb

**Operating Temperature Rating:**

Between -100.0 degrees fahrenheit and 400.0 degrees fahrenheit

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Electrical access port and tamper proof cap

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+100.00/+225.00 actuation point degrees fahrenheit and +99.00/+222.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point hex nut and external actuation point hex nut

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0