## NSN 5930-01-126-8882

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-126-8882

**Overall Length:** 

Between 1.465 inches and 1.510 inches

**Overall Height:** 

0.360 inches

**Body Diameter:** 

0.720 centimeters

**Mounting Slot Width:** 

0.104 inches

**Body Height:** 

0.300 inches

**Distance Between Mounting Facility Centers:** 

Between 0.937 inches and 0.999 inches

**End Application:** 

E-3a acft

**Tempurature Sensing Element Type:** 

Internal sensor

**Operating Tempurature Rating:** 

Between -10.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Mounting Method:** 

Bracket and slot

**Features Provided:** 

Hermetically sealed case

**Contact Action Stimulus:** 

Increase

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally open, momentary action

**Terminal Type:** 

Tab, solder lug

**Contact Load Current Rating:** 

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:** 

140.00 actuation point degrees fahrenheit and 135.00 deactuation point degrees fahrenheit and 138.00 deactuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 5.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

## NSN 5930-01-126-8882

Thermostatic Switch - Page 2 of 2



Style	Design	nator:
Otylo	Design	ilatoi.

Disc w/flange

## **Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-s-24236/20 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0