

View Online at <https://aerobasegroup.com/nsn/5930-01-127-0222>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.360 inches single mounting facility and 0.390 inches single mounting facility

**Overall Length:**

2.000 inches

**First Flat Length:**

0.235 inches single actuator and 0.265 inches single actuator

**Flat Height:**

0.203 inches single actuator and 0.233 inches single actuator

**Shaft Diameter:**

0.235 inches single actuator and 0.265 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Overall Diameter:**

1.624 inches

**Nonturn Device Radius:**

0.526 inches at 12: 00 o'clock and 0.536 inches at 12: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

4 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0