NSN 5930-01-127-1990

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-127-1990

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Water resistant
Overall Length:
3.010 inches
Overall Height:
3.140 inches
Overall Width:
1.020 inches
Actuator Length:
1.560 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.900 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.800 inches
Housing Length:
3.010 inches
Housing Width:
1.020 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.690 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
6.0 ounces
Switch Actuating Force:
20.0 ounces

Actuator Movement:

10.0 pretravel degrees and 6.5 overtravel degrees and 0.5 differential degrees

NSN 5930-01-127-1990

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 30.000 milliamperes inductive dc and 15.000 amperes resistive ac and 4.000 amperes inductive ac

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0