

View Online at <https://aerobasegroup.com/nsn/5930-01-127-1994>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.710 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.110 inches

Actuator Width:

0.620 inches

Actuator Color:

Green single actuator and yellow single actuator and yellow single actuator

Illuminated Actuator Color:

Green single actuator and yellow single actuator and yellow single actuator

Actuator Inscription:

Xmt key single actuator

Illuminated Actuator Color Sequence:

Upper left half of actuator green upper right half of actuator yellow lower half of actuator yellow

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

2.620 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0