

View Online at <https://aerobasegroup.com/nsn/5930-01-127-2001>

Hazardous Locations/environmental Protection:

Dustproof and moisture resistant and salt spray resistant and vibration resistant

Overall Length:

0.988 inches

Overall Height:

0.350 inches

Body Diameter:

0.660 inches

Mounting Slot Width:

0.104 inches

Distance Between Mounting Facility Centers:

Between 0.937 inches and 0.999 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 450.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load first voltage 2.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

186.00 actuation point degrees fahrenheit and 194.00 actuation point degrees fahrenheit and 2.00 differential point degrees fahrenheit and 5.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

120.0 ac at sea level first voltage 30.0 dc at sea level second voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Disc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0