

View Online at <https://aerobasegroup.com/nsn/5930-01-127-3868>

**Thread Class:**

2a

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

2.305 inches

**Overall Height:**

2.375 inches

**Overall Width:**

1.015 inches

**Bushing Length:**

0.980 inches

**Body Length:**

1.660 inches

**Body Width:**

1.015 inches

**Body Height:**

1.000 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.395 inches

**Actuator Free Position Height:**

1.375 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

2350-01-061-2445

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing and unthreaded hole

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes motor dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0