## NSN 5930-01-127-3870

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-127-3870

#### **Body Style:**

Panel mount

#### **Overall Length:**

1.200 inches

#### **Overall Height:**

2.968 inches

#### **Overall Width:**

0.960 inches

#### **Body Length:**

0.844 inches

#### **Body Width:**

0.960 inches

#### **Case Material:**

Metal

#### Actuator Length:

#### 1.040 inches

Actuator Style:

Rectangular

#### Actuator Height:

0.140 inches

#### Actuator Width:

0.800 inches

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

16e1640nuclrw

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

#### **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

5 turret and 6 tab, solder lug

#### Specification Data:

81349-mil-s-22885/9 government specification

### Shelf Life:

NI/o

# NSN 5930-01-127-3870

Push Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

