

View Online at <https://aerobasegroup.com/nsn/5930-01-127-5024>

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level125.0 lowest ac voltage rating at sea level350.0 highest dc voltage rating at sea level120.0 lowest dc voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Contact Load Current Rating:

30.0 amperes resistive load highest ac voltage rating at sea level and 30.0 amperes inductive load highest ac voltage rating at sea level30.0 amperes resistive load lowest ac voltage rating at sea level and 40.0 amperes inductive load lowest ac voltage rating at sea level15.0 amperes resistive load highest dc voltage rating at sea level and 15.0 amperes inductive load highest dc voltage rating at sea level30.0 amperes resistive load lowest dc voltage rating at sea level and 25.0 amperes inductive load lowest dc voltage rating at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0