NSN 5930-01-127-6498

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-127-6498

Overall Length:
5.188 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Capillary Tube Length:
120.0 inches
Bulb Length:
4.500 inches
Bulb Diameter:
0.375 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Intermediate Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
14 single threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.750 inches single threaded hole
Mounting Facility Pattern:
Obtuse triangle
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load third voltage

Contact Adjustability:Actuation point adjustable

NSN 5930-01-127-6498

Thermostatic Switch - Page 2 of 2

Fiig: A048b0



Contact Adjustment Range:
+140.00/+215.00 actuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point screw
Contact Stimulus Rating:
140.00 actuation point degrees fahrenheit and 215.00 actuation point degrees fahrenheit
Contact Voltage Rating In Volts:
550.0 dc at sea level fourth voltage
Frequency In Hertz:
60.0 second voltage
Media For Which Designed:
Liquid
Thread Series Designator:
Npt single threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No