

View Online at <https://aerobasegroup.com/nsn/5930-01-127-6498>

Overall Length:

5.188 inches

Overall Width:

2.812 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Capillary Tube Length:

120.0 inches

Bulb Length:

4.500 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Intermediate Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

14 single threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.750 inches single threaded hole

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes inductive load third voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+140.00/+215.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point screw

Contact Stimulus Rating:

140.00 actuation point degrees fahrenheit and 215.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Liquid

Thread Series Designator:

Npt single threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0