## NSN 5930-01-127-7343

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-127-7343

## **Overall Length:**

0.344 inches

**Overall Height:** 

0.080 inches

## **Body Diameter:**

0.263 inches

**Tempurature Sensing Element Type:** 

Internal sensor

### **Mounting Method:**

Clamp

#### **Features Provided:**

Hermetically sealed case

#### **Contact Action Stimulus:**

Increase

#### Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

## **Terminal Type:**

Wire lead

### **Contact Load Current Rating:**

500.0 milliamperes resistive load second voltage and 500.0 milliamperes inductive load second voltage and 200.0 milliamperes lamp load second voltage

#### **Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

#### **Contact Stimulus Rating:**

255.00 actuation point degrees fahrenheit and 225.00 deactuation point degrees fahrenheit

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

#### **Frequency In Hertz:**

60.0 first voltage

Media For Which Designed:

Gas or liquid

#### Style Designator:

Disc

#### **Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-s-24236/13 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

- **Demilitarization:**

# NSN 5930-01-127-7343

Thermostatic Switch - Page 2 of 2

**Fiig:** A048b0

