

View Online at <https://aerobasegroup.com/nsn/5930-01-127-7415>

Body Style:

Bushing mounted

Actuator Style:

Round

Actuator Diameter:

0.400 inches

Actuator Height:

0.660 inches

Actuator Free Position Height:

2.460 inches

Housing Diameter:

Between 0.625 inches and 0.675 inches

Housing Length:

1.000 inches

Housing Bushing Length:

1.800 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.500 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 4.000 amperes motor dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac and 1.000 amperes lamp ac and 1.000 amperes motor ac

Terminal Type And Quantity:

1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0